

Penetration temperature probe with ergonomical handle

Description



Features

- Ergonomic handle made of PEEK
- Rust and acid resistant stainless steel
- Centric or inclined measuring tip
- Measuring range from -50 °C to +260 °C

Fields of application

- Food inspection
- Meat processing machines
- Freezers
- Cooking machines
- Baking machines
- Cooking and smoking equipment
- Quality assurance in the food industry

Technical data

Penetration temperature probe with ergonomic handle PEEK		
Sensors	Thermocouple Type K, Pt1000, Pt100	
Measuring range	-50...+260 °C	
Measuring tip	Inclined or centric	
Accuracy	Thermocouple Type K, Pt1000, Pt100	DIN EN 60584 Class 1 F0,3 (Class B) DIN EN 60751 conform
Measuring current	max. 0,3 mA	
Type of circuit	2-wire 4-wire	
Tube length	100 mm	
Tube diameter	4 mm	
Material	Tube Handle	Stainless steel 1.4571 PEEK
Handle dimensions	Straight handle Angled handle	(LxB) 40 x 10 mm (LxBxH) 43,8 x 23,3 x 12 mm
Connection	free ends 30mm, uninsulated	
Protection type	IP65	
Cable length	3000 mm	
Environmental data	RoHS- and REACH conform	

Characteristics

Due to their special design, the robust penetration temperature probes from B+B are preferably suitable for cooking, simmering and baking processes in all areas of food processing and preservation.

The B+B penetration temperature probes can be supplied with the following sensor technology: Pt100, Pt1000 or thermocouple type K. The piercing sleeve is made of stainless steel and has an inclined or centric measuring tip. The ergonomic handle made of high-quality PEEK, as well as the connecting cable, ensure a highly hygienic design - the perfect temperature probe for the food industry. This optimized penetration temperature probe is resistant to common household cleaning agents due to the materials used.

Penetration temperature probe with ergonomical handle

Article number overview

Penetration temperature probe with inclined measuring tip					
Article number	Description	Measuring current	Connection	Sensor	Handle
0600 0065-100	Penetration temperature probe 1xPt100/B/4 Pt100	4-wire	4 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Pt100	Straight handle
0600 0066-100	Penetration temperature probe 1xPt1000/B/4 Pt1000	4-wire	4 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Pt1000	Straight handle
0600 0067-100	Penetration temperature probe 1xPt1000/B/4 Pt1000	4-wire	4 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Pt1000	Angled handle

Penetration temperature probe with centric measuring tip					
Article number	Description	Measuring current	Connection	Sensor	Handle
0600 0065-101	Penetration temperature probe 1xPt100/B/4 Pt100	4-wire	4 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Pt100	Straight handle
0600 0066-101	Penetration temperature probe 1xPt1000/B/4 Pt1000	4-wire	4 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Pt1000	Straight handle
0600 0067-101	Penetration temperature probe 1xPt1000/B/4 Pt1000	4-wire	4 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Pt1000	Angled handle
0600 1112-101	Penetration temperature probe 1x K with centric penetration tip	2-wire	2 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Thermocouple Type K	Straight handle
0600 1114-101	Penetration temperature probe 1x K with centric penetration tip	2-wire	2 x 0,22 mm ² , PTFE/shielding/PTFE Coat color white	Thermocouple Type K	Angled handle